Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-200-0413

**Cross Sectional Shape:** 

Round

**Thread Class:** 

3b 1st end

**Thread Direction:** 

Right-hand 1st end

Inside Diameter:

0.250 inches

**Tempurature Rating:** 

-65.0 degrees fahrenheit and 158.0 degrees fahrenheit single response

#### **Outside Diameter:**

0.500 inches

Minimum Inside Bending Radius:

4.000 inches

#### Hose Or Tubing Specification/std Data:

Mil mil-h-5593, size no. 4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### First End Fitting Specification/std Data:

Mil ms27404-4d standard (includes industry or association standards, individual manufactureer standards, etc.).

## Connection Style:

Swivel nut flare 1st end

#### End Connection Design:

Straight 1st end

#### End Fitting Component And Material:

Complete fitting aluminum alloy all ends

#### Fitting Component And Surface Treatment:

Complete fitting anodize 1st end

#### **Connection Type:**

Threaded internal tube 1st end

#### Second End Relationship With First End:

Identical

## Burst Test Pressure:

1250.0 pounds per square inch

## First End Swivel Action Capability:

Not included

## Layer Composition And Location:

Outer layer molded rubber, synthetic

## Maximum Operating Pressure:

200.0 pounds per square inch

### Thread Size:

0.438 inches 1st end

## Seat Angle:

37.0 degrees 1st end

# NSN 4720-00-200-0413

Nonmetallic Hose Assembly - Page 2 of 2



Hydrostatic Test Pressure: 400.0 pounds per square inch **Outer Covering Environmental Protection:** Abrasion resistant and fuel resistant and oil resistant **Inside Surface Condition:** Smooth Measuring Method And Length: 11.000 inches working **Special Features:** Inner conveying tube material-rubber, synthetic Media For Which Designed: Air and fuel/oil, hydrocarbon single response **Thread Series Designator:** Unjf 1st end **Specification Data:** 88044-an6270 government standard Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A542a0