Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-200-0425

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.250 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit and 158.0 degrees fahrenheit single response	
Outside Diameter:	
0.500 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Burst Test Pressure:	
1250.0 pounds per square inch	
Layer Composition And Location:	
Outer layer molded rubber, synthetic and 1st layer braided cotton cord	
Maximum Operating Pressure:	
200.0 pounds per square inch	
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
400.0 pounds per square inch	
Outer Covering Environmental Protection:	
Fuel resistant and oil resistant and water resistant	
Vacuum In Torr:	
504.0	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
12.000 inches working	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Unf 1st end	

Nonmetallic Hose Assembly - Page 2 of 2

Specification Data:

88044-an6270 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

