NSN 4720-00-202-6483

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-202-6483

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.000 inches
Tempurature Rating:
212.0 degrees fahrenheit single response
Minimum Inside Bending Radius:
6.000 inches
Connection Style:
Swivel nut, gasket seal 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal hose 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
300.0 pounds per square inch
Layer Composition And Location:
1st layer helix corrosion resistant steel coil and 2nd layer rubber impregnated fabric and outer layer molded rubber, ethylene propylene
Thread Size:
1.000 inches 2nd end
Hydrostatic Test Pressure:
100.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and ozone resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
300.000 inches excluding end fittings
Special Features:
Female fitting with synthetic rubber washer and hexagon wrenching feature
Special Markings:
Water, suction
Media For Which Designed:
Water, fresh single response
Thread Series Designator:
Npsh 2nd end

81348-zz-h-561 government specification

Specification Data:

NSN 4720-00-202-6483

Nonmetallic Hose Assembly - Page 2 of 2



Sı	oec	ific	catio	า Or	Sta	ndar	d:
----	-----	------	-------	------	-----	------	----

B grade and i class and a style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0