

Nonmetallic Hose Assembly - Page 1 of 2	Grou
View Online at https://aerobasegroup.com/nsn/4720-00-202-6483	
Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
1.000 inches	
Tempurature Rating:	
212.0 degrees fahrenheit single response	
Minimum Inside Bending Radius:	
6.000 inches	
Connection Style:	
Swivel nut, gasket seal 1st end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded internal hose 1st end	
Features Provided:	
Electrostatic discharge capability	
Burst Test Pressure:	
300.0 pounds per square inch	
Layer Composition And Location:	
1st layer helix corrosion resistant steel coil and 2nd layer rubber impregnated fabric and outer layer	molded rubber, ethylene propylene
Thread Size:	
1.000 inches 2nd end	
Hydrostatic Test Pressure:	
100.0 pounds per square inch	
Outer Covering Environmental Protection:	
Oil resistant and ozone resistant and weatherproof	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
300.000 inches excluding end fittings	
Special Features:	
Female fitting with synthetic rubber washer and hexagon wrenching feature	
Special Markings:	
Water, suction	
Media For Which Designed:	
Water, fresh single response	
Thread Series Designator:	
Npsh 2nd end	
Specification Data:	

81348-zz-h-561 government specification

Nonmetallic Hose Assembly - Page 2 of 2



## **Specification Or Standard:**

B grade and i class and a style

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0