## NSN 4720-00-202-6726

**Cross Sectional Shape:** 

1 class

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-202-6726

Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response
Connection Style:
Plain 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external pipe 2nd end
Burst Test Pressure:
900.0 pounds per square inch
Layer Composition And Location:
1st layer braided fiber and 2nd layer braided fiber and outer layer molded rubber, synthetic
Maximum Operating Pressure:
150.0 pounds per square inch
Thread Size:
0.750 inches 2nd end
Hydrostatic Test Pressure:
300.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and ozone resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
150.000 inches excluding end fittings
Special Features:
Couplings attached w/two bolt finger type clamps
Special Markings:
Gnone
Media For Which Designed:
Air single response
Thread Series Designator:
Npt 1st end
Specification Data:
81348-zz-h-500 government specification
Specification Or Standard:

## NSN 4720-00-202-6726

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0