Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-202-6726

Cross Sect	ional Shape:
Round	
Thread Dire	ection:
Right-hand	1st end
Inside Diam	neter:
0.500 inches	3
Tempuratu	re Rating:
-40.0 degree	es fahrenheit single response
Connection	Style:
Plain 2nd er	nd
End Conne	ction Design:
Straight 2nd	end
Connection	Туре:
Threaded ex	ternal pipe 2nd end
Burst Test	Pressure:
900.0 pound	ls per square inch
Layer Com	position And Location:
1st layer bra	ided fiber and 2nd layer braided fiber and outer layer molded rubber, synthetic
Maximum C	Operating Pressure:
150.0 pound	ls per square inch
Thread Size	e:
0.750 inches	s 2nd end
-lydrostatic	Test Pressure:
300.0 pound	ls per square inch
Outer Cove	ring Environmental Protection:
Oil resistant	and ozone resistant
Inside Surf	ace Condition:
Smooth	
Measuring	Method And Length:
150.000 incl	nes excluding end fittings
Special Fea	tures:
Couplings a	ttached w/two bolt finger type clamps
Special Ma	rkings:
Gnone	
Media For V	Vhich Designed:
Air single re	sponse
Thread Ser	ies Designator:
Npt 1st end	
Specificatio	on Data:
-	500 government specification
	on Or Standard:

## NSN 4720-00-202-6726

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

