Nonmetallic Hose Assembly - Page 1 of 1



	uivup
Viev	v Online at https://aerobasegroup.com/nsn/4720-00-202-6732
Cro	ss Sectional Shape:
Rou	Ind
Thr	ead Direction:
Rigl	nt-hand 1st end
Insi	de Diameter:
1.50	00 inches
Cor	nection Style:
Swi	vel nut, gasket seal 1st end
Enc	I Connection Design:
Stra	ight 2nd end
Cor	nection Type:
Thre	eaded internal hose 1st end
Bur	st Test Pressure:
450	.0 pounds per square inch
Lay	er Composition And Location:
Out	er layer wrapped rubber, synthetic and 1st layer rubber impregnated fabric
Thr	ead Size:
1.50	00 inches 2nd end
Нус	Irostatic Test Pressure:
150	.0 pounds per square inch
Insi	de Surface Condition:
Smo	poth
Mea	asuring Method And Length:
300	.000 inches excluding end fittings
Spe	cial Features:
Cou	plings attached with clamp on each end ofhose female swivel coupling has guard pin or rocker lug wrenching feature, hose branded with
wor	d water
Med	lia For Which Designed:
Wat	er, fresh single response
Thr	ead Series Designator:
Nps	h 2nd end
Spe	cification Data:
813	48-zz-h-601 government specification
Spe	cification Or Standard:
1 gr	ade and 1 class
She	If Life:
N/a	
Uni	t Of Measure:
Der	nilitarization:
No	
Fiig	:
A54	2a0