Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-202-6945

**Cross Sectional Shape:** 

Round

Inside Diameter:

0.750 inches

**Tempurature Rating:** 

-40.0 degrees fahrenheit single response

**Outside Diameter:** 

1.469 inches

**Quick Disconnect Size:** 

0.750 inches 1st end

**Connection Style:** 

Universal 1st end

**Connection Type:** 

Universal quick disconnect 1st end

**Burst Test Pressure:** 

700.0 pounds per square inch

## Layer Composition And Location:

1st layer rubber impregnated woven fabric and 1st layer rubber impregnated braided fabric or 2nd layer rubber impregnated braided fabric

or outer layer molded rubber, synthetic

Maximum Operating Pressure:

125.0 pounds per square inch

## Hydrostatic Test Pressure:

250.0 pounds per square inch

**Outer Covering Environmental Protection:** 

Oil resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

300.000 inches excluding end fittings

**Special Features:** 

Couplings attached w/2 bolt finger type clamps

Media For Which Designed:

Air single response

**Specification Data:** 

81348-zz-h-500 government specification

Specification Or Standard:

1 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

## NSN 4720-00-202-6945

Nonmetallic Hose Assembly - Page 2 of 2

**Fiig:** A542a0

