Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-202-7835

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.313 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.672 inches
Minimum Inside Bending Radius:
4.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided steel wire and outer layer rubber impregnated cotton fabric and 1st layer braided cotton cord
Maximum Operating Pressure:
2000.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
4500.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
39.000 inches working
Thread Series Designator:
Unf 1st end
Specification Data:
96906-ms28741 government standard
Shelf Life:
N/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0