NSN 4720-00-202-8364

Cross Sectional Shape:

Round

Thread Class: 2a 1st end

Thread Direction:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-202-8364

Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 180.0 degrees fahrenheit single response
Outside Diameter:
Between 0.344 inches and 0.375 inches
Connection Style:
Swivel nut, inverted flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external tube 1st end
Thready Qty Per Inch (tpi):
24 1st end
Burst Test Pressure:
2000.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic and 1st layer braided fabric
Maximum Operating Pressure:
500.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
45.0 degrees 1st end
Hydrostatic Test Pressure:
1000.0 pounds per square inch
Outer Covering Environmental Protection:
Hydraulic solution resistant and oil resistant and water resistant
Vacuum In Torr:
254.0
Inside Surface Condition:
Smooth
Media For Which Designed:
Alcohol, methyl and ethylene glycol and fuel/oil, hydrocarbon and water, fresh single response
Thread Series Designator:
Uns 1st end

NSN 4720-00-202-8364

Nonmetallic Hose Assembly - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0