

View Online at <https://aerobasegroup.com/nsn/4720-00-202-8657>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

1.500 inches

**Hose Or Tubing Specification/std Data:**

A-a-59567, , grade 1, class 1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**First End Fitting Specification/std Data:**

A-a-59567 type 1, class aa, style1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Second End Fitting Specification/std Data:**

Ww-c-624, type aa, style 1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Connection Style:**

Swivel nut, gasket seal 1st end

**End Connection Design:**

Straight 2nd end

**End Fitting Component And Material:**

Complete fitting copper alloy all ends

**Connection Type:**

Threaded internal hose 1st end

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

450.0 pounds per square inch

**First End Swivel Action Capability:**

Included

**Layer Composition And Location:**

Outer layer molded rubber, synthetic

**Thread Size:**

1.500 inches 2nd end

**Hydrostatic Test Pressure:**

250.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

600.000 inches excluding end fittings

**Second End Swivel Action Capability:**

Not included

**Special Features:**

**Thread Series Designator:**

Npsh 2nd end

**Specification Data:**

58536-a-a-59567 government specification

**Specification Or Standard:**

1 class and 1 grade

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0