## NSN 4720-00-202-8657

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-202-8657

**Cross Sectional Shape:** 

Round

**Thread Direction:** 

Right-hand 1st end

Inside Diameter:

1.500 inches

## **Hose Or Tubing Specification/std Data:**

A-a-59567, grade 1, class 1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### First End Fitting Specification/std Data:

A-a-59567 type 1, class aa, style1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### Second End Fitting Specification/std Data:

Ww-c-624, type aa, style 1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Connection Style:**

Swivel nut, gasket seal 1st end

## **End Connection Design:**

Straight 2nd end

#### **End Fitting Component And Material:**

Complete fitting copper alloy all ends

#### **Connection Type:**

Threaded internal hose 1st end

## Second End Relationship With First End:

Not identical

#### **Burst Test Pressure:**

450.0 pounds per square inch

## First End Swivel Action Capability:

Included

#### **Layer Composition And Location:**

Outer layer molded rubber, synthetic

#### **Thread Size:**

1.500 inches 2nd end

## **Hydrostatic Test Pressure:**

250.0 pounds per square inch

## **Inside Surface Condition:**

Smooth

## Measuring Method And Length:

600.000 inches excluding end fittings

## Second End Swivel Action Capability:

Not included

. . . . .

# NSN 4720-00-202-8657

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Npsh 2nd end
Specification Data:
58536-a-a-59567 government specification
Specification Or Standard:
1 class and 1 grade
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0