---

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-202-9618

Cross Sectional Shape:
Round
Fhread Direction:
Right-hand 1st end
nside Diameter:
.250 inches
Dutside Diameter:
.875 inches
Connection Style:
Swivel nut, gasket seal 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal pipe 2nd end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
300.0 pounds per square inch
ayer Composition And Location:
Duter layer rubber impregnated braided rayon cord and 1st layer braided cotton cord
Thread Size:
.250 inches 2nd end
lydrostatic Test Pressure:
300.0 pounds per square inch
Duter Covering Environmental Protection:
Fuel resistant and water resistant
nside Surface Condition:
Smooth
leasuring Method And Length:
500.000 inches
Nedia For Which Designed:
Fuel/oil, hydrocarbon and water, fresh single response
Thread Series Designator:
Npt 1st end
Specification Data:
31349-mil-h-6615 government specification
Specification Or Standard:
type
Shelf Life:
l/a
Jnit Of Measure:

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

