NSN 4720-00-203-0906

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-203-0906

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Outside Diameter:
0.719 inches
Exterior Color:
Black
Hose Or Tubing Specification/std Data:
Zz-h-461 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting copper alloy all ends
Connection Type:
Threaded external pipe 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
700.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
2nd layer braided cotton cord
Thread Size:
0.250 inches 1st end
Hydrostatic Test Pressure:
250.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
36.000 inches excluding end fittings
Special Features:
Inner conveying tube material-rubber, synthetic
Media For Which Designed:

Npt 1st end

Air single response

Thread Series Designator:

NSN 4720-00-203-0906

Nonmetallic Hose Assembly - Page 2 of 2



\r		•	C 2 t	ınn	11212	Į
OL.	, .		Cal	UII	Data	,

Zz-h-461 professional/industrial association specification and 81348-zz-h-461 government specification

Specification Or Standard:

A style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0