NSN 4720-00-203-0906

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-203-0906

| Cross Sectional Shape: |
|---|
| Round |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.375 inches |
| Outside Diameter: |
| 0.719 inches |
| Exterior Color: |
| Black |
| Hose Or Tubing Specification/std Data: |
| Zz-h-461 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Connection Style: |
| Plain 1st end |
| End Connection Design: |
| Straight 1st end |
| End Fitting Component And Material: |
| Complete fitting copper alloy all ends |
| Connection Type: |
| Threaded external pipe 1st end |
| Second End Relationship With First End: |
| Identical |
| Burst Test Pressure: |
| 700.0 pounds per square inch |
| First End Swivel Action Capability: |
| Not included |
| Layer Composition And Location: |
| 2nd layer braided cotton cord |
| Thread Size: |
| 0.250 inches 1st end |
| Hydrostatic Test Pressure: |
| 250.0 pounds per square inch |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 36.000 inches excluding end fittings |
| Special Features: |
| Inner conveying tube material-rubber, synthetic |
| Media For Which Designed: |

Npt 1st end

Air single response

Thread Series Designator:

NSN 4720-00-203-0906

Nonmetallic Hose Assembly - Page 2 of 2



| ~n | ΔC IT | 100 | HINE | 1 1 1 | 212 |
|----|---------------|-----|-------|--------------|------|
| JU | CUII | 166 | ıtior | · | ala. |
| | | | | | |

Zz-h-461 professional/industrial association specification and 81348-zz-h-461 government specification

Specification Or Standard:

A style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0