

View Online at <https://aerobasegroup.com/nsn/4720-00-203-1033>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

0.500 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

**Outside Diameter:**

Between 0.875 inches and 0.937 inches

**Minimum Inside Bending Radius:**

7.000 inches

**Burst Test Pressure:**

8000.0 pounds per square inch single response

**Layer Composition And Location:**

1st layer braided wire err-100

**Maximum Operating Pressure:**

2000.0 pounds per square inch single response

**Hydrostatic Test Pressure:**

4000.0 pounds per square inch single response

**Outer Covering Environmental Protection:**

Fire resistant and oil resistant and ozone resistant and mildew resistant

**Inside Surface Condition:**

Smooth

**Material:**

Rubber synthetic tube

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Specification Data:**

81349-mil-h-13531 government specification

**Specification Or Standard:**

1 type and a class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A541z0

**Mil-std (military Standard):**

Mil-h-13531 spec.