NSN 4720-00-203-2506

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-203-2506

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.500 inches
Connection Style:
Swivel nut with loose or integral clinch sleeve 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
1600.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic and 1st layer braided cotton cord
Maximum Operating Pressure:
Maximum Operating Pressure: 400.0 pounds per square inch
400.0 pounds per square inch
400.0 pounds per square inch Thread Size:
400.0 pounds per square inch Thread Size: 0.500 inches 1st end
400.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle:
400.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle: 40.0 degrees 1st end
400.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle: 40.0 degrees 1st end Hydrostatic Test Pressure:
400.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle: 40.0 degrees 1st end Hydrostatic Test Pressure: 800.0 pounds per square inch
400.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle: 40.0 degrees 1st end Hydrostatic Test Pressure: 800.0 pounds per square inch Inside Surface Condition:
400.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle: 40.0 degrees 1st end Hydrostatic Test Pressure: 800.0 pounds per square inch Inside Surface Condition: Smooth
400.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle: 40.0 degrees 1st end Hydrostatic Test Pressure: 800.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length:
400.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle: 40.0 degrees 1st end Hydrostatic Test Pressure: 800.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 48.000 inches
400.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle: 40.0 degrees 1st end Hydrostatic Test Pressure: 800.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 48.000 inches Media For Which Designed:
400.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle: 40.0 degrees 1st end Hydrostatic Test Pressure: 800.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 48.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response
400.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle: 40.0 degrees 1st end Hydrostatic Test Pressure: 800.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 48.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator:
400.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle: 40.0 degrees 1st end Hydrostatic Test Pressure: 800.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 48.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end

--

NSN 4720-00-203-2506

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0