

View Online at <https://aerobasegroup.com/nsn/4720-00-203-2528>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Temperature Rating:

-65.0 degrees fahrenheit and 235.0 degrees fahrenheit single response

Outside Diameter:

0.438 inches

Minimum Inside Bending Radius:

2.000 inches

Exterior Color:

Black

Connection Style:

Swivel nut, inverted flare 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal pipe 1st end

Burst Test Pressure:

2000.0 pounds per square inch

Layer Composition And Location:

2nd layer braided rayon cord and outer layer molded rubber, synthetic and 1st layer braided rayon cord

Maximum Operating Pressure:

500.0 pounds per square inch

Thread Size:

0.250 inches 2nd end

Seat Angle:

45.0 degrees 1st end

Hydrostatic Test Pressure:

1000.0 pounds per square inch

Outer Covering Environmental Protection:

Grease resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

11.250 inches

Special Features:

Furnished with one straight coupling

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0