NSN 4720-00-203-2534



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-203-2534 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 0.562 inches **Minimum Inside Bending Radius:** 3.000 inches **Exterior Color:** Black **Connection Style:** Plain 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 27 2nd end **Burst Test Pressure:** 5000.0 pounds per square inch **Layer Composition And Location:** 2nd layer braided rayon cord and outer layer molded rubber, synthetic and 1st layer braided rayon cord **Maximum Operating Pressure:** 1250.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 45.0 degrees 1st end **Hydrostatic Test Pressure:**

2500.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and light resistant and oil resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

18.000 inches

NSN 4720-00-203-2534

Nonmetallic Hose Assembly - Page 2 of 2



N	Λ	edia	For	Which	Design	ned:

Fuel/oil, hydrocarbon and water, fresh single response

Thread Series Designator:

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0