NSN 4720-00-203-2696

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-203-2696

Cross Sectional Shape:
Cross Sectional Shape: Round
Thread Class:
2a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.312 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.625 inches
Connection Style:
Swivel nut, inverted flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external tube 1st end
Thready Qty Per Inch (tpi):
18 1st end
Burst Test Pressure:
700.0 pounds per square inch
Layer Composition And Location:
2nd layer braided cotton cord and outer layer molded rubber, chloroprene and 1st layer braided cotton cord
Thread Size:
0.625 inches 1st end
Seat Angle:
37.0 degrees 1st end
Outer Covering Environmental Protection:
Oil resistant and ozone resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
7.375 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4720-00-203-2696

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0