Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-203-2894

Cross Section	al Shape:
Round	
Thread Directi	on:
Right-hand 1st	end
Inside Diamete	er:
1.000 inches	
Tempurature F	Rating:
-40.0 degrees f	ahrenheit and 200.0 degrees fahrenheit single response
Outside Diame	eter:
1.562 inches	
Exterior Color	:
Black	
Connection St	yle:
Plain 1st end	
End Connection	on Design:
Straight 1st end	t de la construcción de la const
Connection Ty	/pe:
Threaded exter	nal pipe 1st end
Burst Test Pre	essure:
7500.0 pounds	per square inch
Layer Compos	sition And Location:
Outer layer mo	lded rubber, synthetic and 2nd layer braided steel wire and 3rd layer braided steel wire
Maximum Ope	erating Pressure:
1875.0 pounds	per square inch
Thread Size:	
1.000 inches 1	st end
Hydrostatic Te	est Pressure:
3750.0 pounds	per square inch
Inside Surface	Condition:
Smooth	
Measuring Me	thod And Length:
34.000 inches	
Media For Whi	ich Designed:
Hydraulic fluid,	phosphate-ester base and hydraulic fluid, silicate-ester base and fuel/oil, hydrocarbon single response
Thread Series	Designator:
Nptf 1st end	
Shelf Life:	
N/a	
Unit Of Measu	re:
Demilitarizatio	on:
No	

## NSN 4720-00-203-2894

Nonmetallic Hose Assembly - Page 2 of 2

**Fiig:** A542a0

