

View Online at <https://aerobasegroup.com/nsn/4720-00-203-3023>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

3.000 inches

**Temperature Rating:**

-67.0 degrees fahrenheit single response

**Outside Diameter:**

3.625 inches

**First End Fitting Specification/std Data:**

Mil mil-c-38404, class 1, type 1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Connection Style:**

Plain 1st end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting copper alloy all ends

**Connection Type:**

Threaded external pipe 1st end

**Features Provided:**

Electrostatic discharge capability

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

600.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

Outer layer molded rubber, chloroprene

**Thread Size:**

3.000 inches 1st end

**Hydrostatic Test Pressure:**

250.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

120.000 inches

**Special Features:**

Inner conveying tube material-rubber, synthetic

**Special Markings:**

Longitudinal broken yellow stripe

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Npt 1st end

**Specification Data:**

Mil mil-c-38404, class 1, type 1 professional/industrial association specification and 81349-mil-h-6615 government specification

**Fsc Application Data:**

Ground refueling trailer

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0