Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-203-6525

Cross Sectional Shape:		
Round		
Thread Class:		
2a 1st end		
Thread Direction:		
Right-hand 1st end		
Inside Diameter:		
0.188 inches		
Outside Diameter:		
0.422 inches		
Connection Style:		
Swivel nut, inverted flare 1s	end	
End Connection Design:		
Straight 2nd end		
Connection Type:		
Threaded external tube 1st e	nd	
Thready Qty Per Inch (tpi):		
24 1st end		
Burst Test Pressure:		
1200.0 pounds per square ir	ch	
Layer Composition And Lo	cation:	
Outer layer molded rubber,	ynthetic and 1st layer woven fabric	
Maximum Operating Press	ıre:	
300.0 pounds per square inc	1	
Thread Size:		
0.438 inches 1st end		
Seat Angle:		
45.0 degrees 1st end		
Hydrostatic Test Pressure		
600.0 pounds per square inc	1	
Outer Covering Environme	ntal Protection:	
Fuel resistant and oil resista	t and water resistant	
Inside Surface Condition:		
Smooth		
Measuring Method And Le	igth:	
48.000 inches		
Media For Which Designed	:	
Fuel/oil, hydrocarbon single	response	
Thread Series Designator:		
Uns 1st end		
Shelf Life:		
N/a		

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0