NSN 4720-00-203-6526

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-203-6526 **Cross Sectional Shape:** Round **Thread Class:** 2a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.188 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.375 inches **Minimum Inside Bending Radius:** 1.250 inches **Exterior Color:** Black **Connection Style:** Swivel nut, inverted flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded external tube 1st end Thready Qty Per Inch (tpi): 24 1st end **Burst Test Pressure:** 1200.0 pounds per square inch **Layer Composition And Location:** Outer layer molded rubber, synthetic and 1st layer woven cotton cord **Maximum Operating Pressure:** 300.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 45.0 degrees 1st end **Hydrostatic Test Pressure:** 600.0 pounds per square inch **Outer Covering Environmental Protection:** Fuel resistant and oil resistant and water resistant

Inside Surface Condition: Smooth **Measuring Method And Length:** 7.000 inches

NSN 4720-00-203-6526

Nonmetallic Hose Assembly - Page 2 of 2



Media	For	Which	Design	ed

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0