NSN 4720-00-203-9513

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-203-9513

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.719 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut, gas 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
20 2nd end
Burst Test Pressure:
700.0 pounds per square inch
Layer Composition And Location:
2nd layer braided cotton cord and outer layer molded rubber, synthetic and 1st layer braided cotton cord
Maximum Operating Pressure:
175.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Hydrostatic Test Pressure:
350.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
180.000 inches excluding end fittings
Seat Radius:
0.196 inches 1st end
Media For Which Designed:

Air single response

NSN 4720-00-203-9513

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Unf 2nd end
Specification Or Standard
A style
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0