

View Online at <https://aerobasegroup.com/nsn/4720-00-203-9515>

Cross Sectional Shape:

Round

Thread Class:

2b and 2a 2nd end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Temperature Rating:

-65.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

Outside Diameter:

Between 0.469 inches and 0.500 inches

Exterior Color:

Black

Connection Style:

Inverted flare 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal and external tube 2nd end

Thready Qty Per Inch (tpi):

24 1st end

Burst Test Pressure:

4500.0 pounds per square inch

Layer Composition And Location:

2nd layer braided cotton cord and outer layer molded rubber, chloroprene and 1st layer braided cotton cord

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

45.0 degrees 1st end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Outer Covering Environmental Protection:

Mildew resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

19.000 inches and 19.250 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Uns 1st end

Specification Or Standard:

1 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-13719 spec.