## NSN 4720-00-204-0586

**Cross Sectional Shape:** 

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-204-0586

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.688 inches
Connection Style:
Inverted flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting copper alloy all ends
Connection Type:
Threaded external pipe 1st end
Second End Relationship With First End:
Identical
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Layer Composition And Location: 2nd layer braided steel wire
2nd layer braided steel wire
2nd layer braided steel wire  Maximum Operating Pressure:
2nd layer braided steel wire  Maximum Operating Pressure: 5000.0 pounds per square inch
2nd layer braided steel wire  Maximum Operating Pressure: 5000.0 pounds per square inch  Thread Size:
2nd layer braided steel wire  Maximum Operating Pressure: 5000.0 pounds per square inch  Thread Size: 0.250 inches 1st end
2nd layer braided steel wire  Maximum Operating Pressure: 5000.0 pounds per square inch  Thread Size: 0.250 inches 1st end  Seat Angle:
2nd layer braided steel wire  Maximum Operating Pressure: 5000.0 pounds per square inch  Thread Size: 0.250 inches 1st end  Seat Angle: 30.0 degrees 1st end
2nd layer braided steel wire  Maximum Operating Pressure: 5000.0 pounds per square inch  Thread Size: 0.250 inches 1st end  Seat Angle: 30.0 degrees 1st end  Outer Covering Environmental Protection:
2nd layer braided steel wire  Maximum Operating Pressure: 5000.0 pounds per square inch  Thread Size: 0.250 inches 1st end  Seat Angle: 30.0 degrees 1st end  Outer Covering Environmental Protection: Oil resistant
2nd layer braided steel wire  Maximum Operating Pressure: 5000.0 pounds per square inch  Thread Size: 0.250 inches 1st end  Seat Angle: 30.0 degrees 1st end  Outer Covering Environmental Protection: Oil resistant Inside Surface Condition:
2nd layer braided steel wire  Maximum Operating Pressure: 5000.0 pounds per square inch  Thread Size: 0.250 inches 1st end  Seat Angle: 30.0 degrees 1st end  Outer Covering Environmental Protection: Oil resistant  Inside Surface Condition: Smooth
2nd layer braided steel wire  Maximum Operating Pressure: 5000.0 pounds per square inch  Thread Size: 0.250 inches 1st end  Seat Angle: 30.0 degrees 1st end  Outer Covering Environmental Protection: Oil resistant  Inside Surface Condition: Smooth  Measuring Method And Length:
2nd layer braided steel wire  Maximum Operating Pressure: 5000.0 pounds per square inch  Thread Size: 0.250 inches 1st end  Seat Angle: 30.0 degrees 1st end  Outer Covering Environmental Protection: Oil resistant  Inside Surface Condition: Smooth  Measuring Method And Length: 300.000 inches
2nd layer braided steel wire  Maximum Operating Pressure: 5000.0 pounds per square inch  Thread Size: 0.250 inches 1st end  Seat Angle: 30.0 degrees 1st end  Outer Covering Environmental Protection: Oil resistant  Inside Surface Condition: Smooth  Measuring Method And Length: 300.000 inches  Special Features:
2nd layer braided steel wire  Maximum Operating Pressure: 5000.0 pounds per square inch  Thread Size: 0.250 inches 1st end  Seat Angle: 30.0 degrees 1st end  Outer Covering Environmental Protection: Oil resistant  Inside Surface Condition: Smooth  Measuring Method And Length: 300.000 inches  Special Features: Inner conveying tube material-rubber, synthetic
2nd layer braided steel wire  Maximum Operating Pressure: 5000.0 pounds per square inch  Thread Size: 0.250 inches 1st end  Seat Angle: 30.0 degrees 1st end  Outer Covering Environmental Protection: Oil resistant Inside Surface Condition: Smooth  Measuring Method And Length: 300.000 inches  Special Features: Inner conveying tube material-rubber, synthetic  Media For Which Designed:

## NSN 4720-00-204-0586

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0