

View Online at <https://aerobasegroup.com/nsn/4720-00-204-2810>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.312 inches

Temperature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

0.625 inches

Minimum Inside Bending Radius:

2.000 inches

Connection Style:

Swivel nut, inverted flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal pipe 1st end

Burst Test Pressure:

1000.0 pounds per square inch

Layer Composition And Location:

2nd layer rubber impregnated braided fabric and outer layer braided cotton cord and 1st layer rubber impregnated braided fabric

Maximum Operating Pressure:

250.0 pounds per square inch

Thread Size:

0.250 inches 1st end

Seat Angle:

30.0 degrees 1st end

Hydrostatic Test Pressure:

400.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and fuel resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

96.000 inches

Special Features:

Furnished with 1 coupler and 1 connector

Media For Which Designed:

Air single response

Thread Series Designator:

Nptf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0