Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-207-1490

Cross Section	onal Shape:
Round	
Thread Class	5:
3b 2nd end	
Thread Direc	tion:
Right-hand 1s	st end
Inside Diame	eter:
0.187 inches	
Tempurature	Rating:
-65.0 degrees	s fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Dian	neter:
0.312 inches	
Minimum Ins	side Bending Radius:
2.000 inches	
Connection S	Style:
Swivel nut fla	re 2nd end
End Connect	tion Design:
Straight 1st e	nd
Connection -	Туре:
Threaded inte	ernal tube 2nd end
Burst Test P	ressure:
12000.0 pour	nds per square inch
Layer Compo	osition And Location:
Outer layer bi	raided corrosion resistant steel wire
Maximum Op	perating Pressure:
1500.0 pound	ds per square inch
Thread Size:	
0.438 inches	2nd end
Seat Angle:	
37.0 degrees	2nd end
Flow Angle:	
90.0 degrees	2nd end
Outer Coveri	ing Environmental Protection:
Corrosion res	istant
Inside Surfac	ce Condition:
Smooth	
Measuring M	lethod And Length:
14.250 inches	s working
Thread Serie	es Designator:
Unf 2nd end	
Shelf Life:	
N/a	

NSN 4720-00-207-1490

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0