Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-209-4507

cound	
hread Class:	
b 1st end	
hread Direction:	
light-hand 1st end	
nside Diameter:	
.312 inches	
empurature Rating:	
65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single	response
Outside Diameter:	
.453 inches	
linimum Inside Bending Radius:	
.000 inches	
connection Style:	
wivel nut flare 1st end	
nd Connection Design:	
traight 1st end	
connection Type:	
hreaded internal tube 1st end	
urst Test Pressure:	
000.0 pounds per square inch	
ayer Composition And Location:	
Outer layer braided corrosion resistant steel wire	
laximum Operating Pressure:	
500.0 pounds per square inch	
hread Size:	
.562 inches 1st end	
eat Angle:	
7.0 degrees 1st end	
nside Surface Condition:	
mooth	
leasuring Method And Length:	
.125 inches working	
hread Series Designator:	
Inf 1st end	
helf Life:	
l/a	
Init Of Measure:	
emilitarization:	

NSN 4720-00-209-4507

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

