A542a0

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-212-0531

| С | ross Sectional Shape: |
|----|--|
| R | ound |
| Т | hread Class: |
| 3 | b 1st end |
| Т | hread Direction: |
| R | ight-hand 1st end |
| In | side Diameter: |
| 0. | 218 inches |
| 0 | utside Diameter: |
| 0. | 468 inches |
| С | onnection Style: |
| S | wivel nut flare 1st end |
| Ε | nd Connection Design: |
| S | traight 2nd end |
| С | onnection Type: |
| Т | hreaded internal tube 1st end |
| Т | hready Qty Per Inch (tpi): |
| 18 | 8 1st end |
| L | ayer Composition And Location: |
| 0 | uter layer molded polytetrafluoroethylene |
| Т | hread Size: |
| 0. | 562 inches 2nd end |
| S | eat Angle: |
| 3 | 7.0 degrees 2nd end |
| In | side Surface Condition: |
| S | mooth |
| Μ | leasuring Method And Length: |
| 1 | 5.750 inches working and 16.000 inches working |
| S | pecial Features: |
| W | /ith chafe guard |
| Μ | ledia For Which Designed: |
| F | uel/oil, hydrocarbon single response |
| Т | hread Series Designator: |
| U | nf 2nd end |
| S | helf Life: |
| Ν | /a |
| U | nit Of Measure: |
| | |
| D | emilitarization: |
| Ν | 0 |
| _ | iig: |