Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-212-6948

Cross	Sectional	Shape:
-------	-----------	--------

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.125 inches

Tempurature Rating:

-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.469 inches

Minimum Inside Bending Radius:

3.000 inches

Exterior Color:

Black

Hose Or Tubing Specification/std Data:

Sae j1401 standard (includes industry or association standards, individual manufactureer standards, etc.).

End Application:

Clark equipment company forklift truck model no. C500y45

Connection Style:

Inverted flare 2nd end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting steel all ends

Fitting Component And Surface Treatment:

Complete fitting cadmium 1st end

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

5000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, synthetic

Thread Size:

0.375 inches 1st end

Seat Angle:

45.0 degrees 1st end

Nonmetallic Hose Assembly - Page 2 of 2



Hydrostatic Test Pressure:
3000.0 pounds per square inch
Outer Covering Environmental Protection:
Weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
12.125 inches
Second End Swivel Action Capability:
Not included
Special Features:
Inner conveying tube material-rubber, synthetic
Media For Which Designed:
Air single response
Thread Series Designator:
Unf 2nd end
Specification Data:
Sae j1401 national std/spec
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0