## NSN 4720-00-212-9684

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-212-9684
Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
1.910 inches
Minimum Inside Bending Radius:
16.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting steel all ends
Fitting Component And Surface Treatment:
Complete fitting cadmium 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
12000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
1st layer spirally laid steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
1.625 inches 1st end
Seat Angle:
37.0 degrees 1st end
Outer Covering Environmental Bretestian

**Outer Covering Environmental Protection:** 

Hydraulic solution resistant and oil resistant

## NSN 4720-00-212-9684

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
Special Features:
Inner conveying tube material-rubber, synthetic
Media For Which Designed:
Hydraulic fluid single response
Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A542a0