Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-214-8102

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.688 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.219 inches
Minimum Inside Bending Radius:
7.750 inches
Exterior Color:
Black
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided steel wire and outer layer molded rubber, chloroprene and 1st layer braided steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
1.062 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and oil resistant
Inside Surface Condition:
Smooth

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 18.575 inches working Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig:

A542a0