

View Online at <https://aerobasegroup.com/nsn/4720-00-215-7977>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.875 inches

Temperature Rating:

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Outside Diameter:

1.219 inches

Minimum Inside Bending Radius:

4.500 inches

Exterior Color:

Black

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability and reusable end fittings

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

1000.0 pounds per square inch

Layer Composition And Location:

Outer layer rubber impregnated fabric and 1st layer braided corrosion resistant steel wire, partial coverage

Maximum Operating Pressure:

250.0 pounds per square inch

Thread Size:

1.312 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

500.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant

Vacuum In Torr:

381.0

Inside Surface Condition:

Smooth

Measuring Method And Length:

33.750 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0