NSN 4720-00-218-9270

Cross Sectional Shape:

Round

Thread Class:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-218-9270

3b 1st end			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
0.219 inches			
Tempurature Rating:			
-40.0 degrees fahrenheit and 156.0 degrees fahrenheit single response			
Outside Diameter:			
0.625 inches			
Minimum Inside Bending Radius:			
3.000 inches			
Connection Style:			
Swivel nut flare 1st end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Features Provided:			
Electrostatic discharge capability			
Thready Qty Per Inch (tpi):			
20 1st end			
Burst Test Pressure:			
16000.0 pounds per square inch			
Layer Composition And Location:			
2nd layer braided steel wire and outer layer molded rubber and 1st layer braided steel wire			
Maximum Operating Pressure:			
3000.0 pounds per square inch			
Thread Size:			
0.438 inches 1st end			
Seat Angle:			
37.0 degrees 1st end			
Hydrostatic Test Pressure:			
8000.0 pounds per square inch			
Outer Covering Environmental Protection:			
Fuel resistant and hydraulic solution resistant and mildew resistant and oil resistant and ozone resistant			
Inside Surface Condition:			
Smooth			
Media For Which Designed:			
Air, and fuel/oil, hydrocarbon single response			

NSN 4720-00-218-9270

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	nator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0