NSN 4720-00-220-2370

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-220-2370

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.625 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.078 inches
Minimum Inside Bending Radius:
6.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Perforated outer cover and reusable end fittings
Thready Qty Per Inch (tpi):
14 1st end
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided cotton cord and outer layer rubber impregnated cotton fabric and 1st layer braided wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
1.062 inches 1st end
Seat Angle:
45.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
72.000 inches
Thread Series Designator:

Uns 1st end

NSN 4720-00-220-2370

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0