

View Online at <https://aerobasegroup.com/nsn/4720-00-224-7450>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.750 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

1.160 inches

Minimum Inside Bending Radius:

9.500 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

9000.0 pounds per square inch

Layer Composition And Location:

2nd layer braided steel wire and outer layer molded rubber, synthetic and 1st layer braided steel wire

Maximum Operating Pressure:

2250.0 pounds per square inch

Thread Size:

1.062 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

4500.0 pounds per square inch

Outer Covering Environmental Protection:

Cold resistant and oil resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

55.250 inches

Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Un 1st end

Specification Or Standard:

12 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0