

View Online at <https://aerobasegroup.com/nsn/4720-00-225-0701>

Cross Sectional Shape:

Round

Thread Class:

2b and 2a 2nd end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.125 inches

Outside Diameter:

0.500 inches

Exterior Color:

Black

Hose Or Tubing Specification/std Data:

Sae 40 r1 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Inverted flare 2nd end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting steel all ends

Connection Type:

Threaded internal tube and external pipe 2nd end

Thready Qty Per Inch (tpi):

24 and 18 2nd end

Second End Relationship With First End:

Not identical

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, synthetic and 2nd layer braided rayon cord

Thread Size:

0.438 inches and 0.625 inches 2nd end

External Protection Type And Location (non-core):

spring guard, round stainless steel coil

Seat Angle:

30.0 degrees 1st end

Outer Covering Environmental Protection:

Weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

25.500 inches and 26.000 inches

Second End Swivel Action Capability:

Not included

Special Features:

External protection type and location- spring guard, round stainless steel coil , inner conveying tube material-rubber, synthetic

Media For Which Designed:

Hydraulic fluid, phosphate-ester base single response

Thread Series Designator:

Uns and unf 2nd end

Specification Data:

Sae 40 r1 national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0