## NSN 4720-00-228-3303

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-228-3303 **Cross Sectional Shape:** Round **Thread Class:** 2a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 240.0 degrees fahrenheit single response **Outside Diameter:** Between 0.719 inches and 0.781 inches **Minimum Inside Bending Radius:** 5.000 inches **Exterior Color:** Black **Connection Style:** Inverted flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded external tube 1st end Thready Qty Per Inch (tpi): 18 1st end **Burst Test Pressure:** 700.0 pounds per square inch **Layer Composition And Location:** 1st layer braided fabric and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 175.0 pounds per square inch **Thread Size:** 0.750 inches 1st end

Seat Angle: 30.0 degrees 1st end **Hydrostatic Test Pressure:** 350.0 pounds per square inch **Outer Covering Environmental Protection:** Oil resistant and ozone resistant **Vacuum In Torr:** 10.0 **Inside Surface Condition:** Smooth

## NSN 4720-00-228-3303

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
15.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon and water single response
Thread Series Designator:
Uns 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0