NSN 4720-00-228-7045



Nonmetallic Hose Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4720-00-228-7045

Cross Sectional Shape:
Round
Thread Class:
2a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.750 inches

Minimum Inside Bending Radius:

5.000 inches

Connection Style:

Swivel nut, inverted flare 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded external tube 1st end

Thready Qty Per Inch (tpi):

18 1st end

Burst Test Pressure:

1000.0 pounds per square inch

Layer Composition And Location:

Outer layer molded rubber, synthetic and 1st layer braided fabric

Maximum Operating Pressure:

250.0 pounds per square inch

Thread Size:

0.750 inches 1st end

Outer Covering Environmental Protection:

Ethylene glycol resistant and fuel resistant and fuel resistant and water resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

10.000 inches

Media For Which Designed:

Air and ethylene glycol and fuel/oil, hydrocarbon and water single response

Thread Series Designator:

Uns 1st end

Shelf Life:

N/a

NSN 4720-00-228-7045

Nonmetallic Hose Assembly - Page 2 of 2



ı	1	:.	~	8.4			
ι	JN	ıτ	OI.	IVI	eа	เรเ	ıre:

--

Demilitarization:

No

Fiig:

A542a0