## NSN 4720-00-229-0664

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-229-0664

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 1.250 inches  |
| Tempurature Rating:   |
| -32.0 degrees celsius and 52.0 degrees celsius single response            |
| Outside Diameter:   |
| 1.875 inches  |
| Exterior Color:   |
| Black   |
| Connection Style:   |
| Swivel nut, gasket seal 2nd end   |
| End Connection Design:  |
| Straight 2nd end  |
| End Fitting Component And Material:                                       |
| Complete fitting copper alloy all ends                                    |
| Connection Type:  |
| Threaded internal hose 2nd end  |
| Second End Relationship With First End:                                   |
| Not identical   |
| Burst Test Pressure:  |
| 500.0 pounds per square inch  |
| First End Swivel Action Capability:                                       |
| Not included  |
| Layer Composition And Location:   |
| 2nd layer helix wire coil   |
| Thread Size:  |
| 1.250 inches 2nd end  |
| Hydrostatic Test Pressure:  |
| 150.0 pounds per square inch  |
| Outer Covering Environmental Protection:                                  |
| Fuel resistant and oil resistant and mildew resistant and ozone resistant |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 900.000 inches excluding end fittings                                     |
| Second End Swivel Action Capability:                                      |
| Not included  |
| Thread Series Designator:   |
| Npsh 2nd end  |

## NSN 4720-00-229-0664

Nonmetallic Hose Assembly - Page 2 of 2



| Sn | ec | ifi | cat | hio | n | Dα | ta |
|----|----|-----|-----|-----|---|----|----|
| JU | てし |     | vai | uv  |   | υa | ιa |

81349-mil-h-370 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0