## NSN 4720-00-229-0665

**Cross Sectional Shape:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-229-0665

Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.250 inches
Tempurature Rating:
-32.0 degrees celsius and 52.0 degrees celsius single response
Outside Diameter:
1.875 inches
Exterior Color:
Black
Connection Style:
Swivel nut, gasket seal 1st end
End Connection Design:
Straight 2nd end
End Fitting Component And Material:
Complete fitting copper alloy all ends
Connection Type:
Threaded internal hose 1st end
Second End Relationship With First End:
Not identical
Burst Test Pressure:
500.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
2nd layer helix wire coil
Thread Size:
1.250 inches 2nd end
Hydrostatic Test Pressure:
150.0 pounds per square inch
Outer Covering Environmental Protection:
Fuel resistant and oil resistant and mildew resistant and ozone resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
600.000 inches excluding end fittings
Second End Swivel Action Capability:
Not included
Thread Series Designator:
Ningle Ond and

Npsh 2nd end

## NSN 4720-00-229-0665

Nonmetallic Hose Assembly - Page 2 of 2



Specii	licat	ion	Data
81340	-mil-	h-37	70 ao

81349-mil-h-370 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-prf-370 spec.