NSN 4720-00-229-0666

Nonmetallic Hose - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-229-0666

| Cross Sectional Shape: |
|--|
| Round |
| Inside Diameter: |
| 1.250 inches |
| Tempurature Rating: |
| -32.0 degrees celsius single response and 52.0 degrees celsius single response |
| Outside Diameter: |
| 1.875 inches |
| Exterior Color: |
| Black |
| Features Provided: |
| Electrostatic discharge capability |
| Burst Test Pressure: |
| 500.0 pounds per square inch single response |
| Layer Composition And Location: |
| 1st layer rubber impregnated braided cotton cord err-100 |
| Maximum Operating Pressure: |
| 150.0 pounds per square inch single response |
| Hydrostatic Test Pressure: |
| 400.0 pounds per square inch single response |
| Outer Covering Environmental Protection: |
| Ozone resistant and fuel resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 300.000 inches |
| Material: |
| Rubber butadiene-acrylonitrile class nbr tube |
| Specification Data: |
| 81349-mil-h-370 government specification |
| Specification Or Standard: |
| 1 type and 4 size |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A541z0 |
| Mil-std (military Standard): |
| Mil-h-370 spec. |