## NSN 4720-00-229-5374

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-229-5374

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Class:   |
| 2a 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.375 inches  |
| Tempurature Rating:   |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response                       |
| Outside Diameter:   |
| 0.844 inches  |
| Minimum Inside Bending Radius:  |
| 5.000 inches  |
| Connection Style:   |
| Inverted flare 1st end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded external pipe 1st end  |
| Burst Test Pressure:  |
| 16000.0 pounds per square inch  |
| Layer Composition And Location:   |
| 2nd layer braided steel wire and outer layer molded rubber and 1st layer braided steel wire |
| Maximum Operating Pressure:   |
| 4000.0 pounds per square inch   |
| Thread Size:  |
| 0.375 inches 1st end  |
| Seat Angle:   |
| 30.0 degrees 1st end  |
| Hydrostatic Test Pressure:  |
| 8000.0 pounds per square inch   |
| Outer Covering Environmental Protection:  |
| Oil resistant and weatherproof  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 84.000 inches   |
| Media For Which Designed:   |
| Fuel/oil, hydrocarbon single response   |
| Thread Series Designator:   |
| Notf 1st end  |

Nptf 1st end

## NSN 4720-00-229-5374

Nonmetallic Hose Assembly - Page 2 of 2



| _ |   |            |   |    |    |
|---|---|------------|---|----|----|
| • | n | <b>0</b> 1 | • | 12 | e: |
|   |   |            |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0