NSN 4720-00-229-5376

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-229-5376

Cross Sectional Shape:				
Round				
Thread Class:				
2a 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.375 inches				
Tempurature Rating:				
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response				
Outside Diameter:				
0.844 inches				
Minimum Inside Bending Radius:				
5.000 inches				
Exterior Color:				
Black				
Connection Style:				
Inverted flare 1st end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded external pipe 1st end				
Burst Test Pressure:				
16000.0 pounds per square inch				
Layer Composition And Location:				
2nd layer braided wire and outer layer molded rubber, synthetic and 1st layer braided wire				
Maximum Operating Pressure:				
4000.0 pounds per square inch				
Thread Size:				
0.375 inches 1st end				
Seat Angle:				
30.0 degrees 1st end				
Hydrostatic Test Pressure:				
8000.0 pounds per square inch				
Outer Covering Environmental Protection:				
Oil resistant and weatherproof				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
36.000 inches				
Media For Which Designed:				

Fuel/oil, hydrocarbon single response

NSN 4720-00-229-5376

Nonmetallic Hose Assembly - Page 2 of 2



_	brood	Carias	Docionatori
ı	meau	oenes	Designator:

Nptf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0