NSN 4720-00-229-7020



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-229-7020 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.437 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response **Outside Diameter:** 0.687 inches **Minimum Inside Bending Radius:** 5.750 inches **Connection Style:** Swivel nut, flareless 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 12000.0 pounds per square inch **Layer Composition And Location:** 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer braided corrosion resistant steel wire and 1st layer braided steel wire **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.750 inches 1st end

Seat Angle:

12.0 degrees 1st end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

18.625 inches working

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

NSN 4720-00-229-7020

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0