NSN 4720-00-230-1729

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-230-1729	
Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.188 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit single response and 350.0 degrees fahrenheit single response	
Outside Diameter:	
0.313 inches	
Minimum Inside Bending Radius:	
2.000 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Electrostatic discharge capability	
Burst Test Pressure:	
12000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer braided corrosion resistant steel wire	
Maximum Operating Pressure:	
1500.0 pounds per square inch	
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
3000.0 pounds per square inch	
Outer Covering Environmental Protection:	
Corrosion resistant	

Unjf 1st end

Smooth

Inside Surface Condition:

Thread Series Designator:

5.000 inches working

Measuring Method And Length:

NSN 4720-00-230-1729

Nonmetallic Hose Assembly - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

76301-32-721560-178 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0