

View Online at <https://aerobasegroup.com/nsn/4720-00-230-6515>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

4.000 inches

**Connection Style:**

Swivel nut, gasket seal 2nd end

**End Connection Design:**

Straight 2nd end

**End Fitting Component And Material:**

Complete fitting copper alloy all ends

**Fitting Component And Surface Treatment:**

Complete fitting cadmium and complete fitting zinc 1st end

**Connection Type:**

Threaded internal hose 2nd end

**Features Provided:**

Electrostatic discharge capability

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

600.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

1st layer molded rubber, chloroprene

**Maximum Operating Pressure:**

150.0 pounds per square inch

**Unable To Decode:**

Unable to decode or unable to decode

**Thread Size:**

4.000 inches 2nd end

**Hydrostatic Test Pressure:**

250.0 pounds per square inch

**Outer Covering Environmental Protection:**

Abrasion resistant and light resistant and mildew resistant and oil resistant and ozone resistant and weatherproof

**Unable To Decode:**

Unable to decode or unable to decode

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

120.000 inches excluding end fittings

**Second End Swivel Action Capability:**

Not included

**Special Features:**

Inner conveying tube material-rubber, synthetic

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Npt 1st end

**Specification Data:**

81349-mil-h-17505 government specification

**Specification Or Standard:**

A type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0