

View Online at <https://aerobasegroup.com/nsn/4720-00-230-6516>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

4.000 inches

Connection Style:

Swivel nut, gasket seal 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal hose 1st end

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

600.0 pounds per square inch

Layer Composition And Location:

1st layer molded rubber, chloroprene and 2nd layer rubber impregnated woven fabric and 3rd layer helix wire coil and 4th layer rubber impregnated woven fabric and outer layer molded rubber, chloroprene

Maximum Operating Pressure:

150.0 pounds per square inch

Thread Size:

4.000 inches 2nd end

Hydrostatic Test Pressure:

250.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

360.000 inches excluding end fittings

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Nh-spcl 1st end

Specification Data:

81349-mil-h-17505 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0